
In addition to features of multi-function device on previous page:

- > Two changeover contacts
- > Built-in connection for a potentiometer allows for remote timing adjustments



ETR4 Multi-Function Electronic Timing Relay with Two Changeover Contacts

ETH- Multi-Function Electronic Finning Relay With Two Changeover Contacts										
	Selectable Time Ranges			Actuatin	g Voltage					
					AC					
Description	Seconds	Minutes	Hours	DC	50/60 Hz	Catalog Number	Price			
Selectable time range, multiple functions With two changeover contacts and connection for potentiometer. Can be converted to two timed contacts or one non-delayed and one timed contact. See this page and next page for function diagrams and schematics	0.5 - 10 $1.5 - 30$ $5 - 100$.5 500		24 – 240	24 – 240	ETR4-70-A				



UL/CSA Rating Codes (per UL508 and CSA 22.2 No.14-95)

UL/CSA Co	Continuous Amps	Circuit Voltage									1/4	
		120VAC		240VAC		480VAC		600VAC		VA		
		Make	Break	Make	Break	Make	Break	Make	Break	Make	Break	
B300	5	30	3	15	1.5	-	-	_	-	3600	360	

NOTE: This table represents minimum requirements to achieve a rating of B300. All Moeller series timing relays meet or exceed these standards.



G30

Dimensions are in millimeters.


Not intended for manufacturing purposes.



Industrial Relays

Electronic Timing Relays

DILET... with Sealable Shroud HDILE



Electronic Timing Relays

ETR2...

