Manual Motor

- > Approved by UL 508/CSA C 22.2 No. 14 for use as a manual motor starter, tap conductor protector and Type E combination motor controller
- > Suitable for use in group motor applications
- > Common accessories with PKZM01, PKZM0 and PKZM0-T series helps reduce inventories
- > Phase failure sensitive and ambient compensated
- > Rotary handle operation



See Next Page for **UL/CSA Application** Ratings Guide

## Manual motor controller for larger applications type PKZM4

Rated Un-	Setting 1		Maximum Motor Rating									
interrupted Current	Overload Releases (yellow dial)	Short- Circuit Releases	- Typical Single Phase [HP]			Typical Three Phase [HP]						
$I_{e}$	$I_{r}$	$I_{\sf rm}$										
[A]	[A]	[A]	115V	200V	240V	200V	240V	480V	600V	Catalog Number	Price	
16	10 – 16	224	1	2	3	3	5	10	15	PKZM4-16		
25	16 – 25	350	2	3	2	7½	7½	15	20	PKZM4-25		
32	25 – 32	448	3	5	5	10	10	25	30	PKZM4-32		
40	32 – 40	560	3	5	7½	10	_	30	30	PKZM4-40		
50	40 – 50	700	_	_	_	_	15	30	40	PKZM4-50		
52	50 – 58 2	812	_	_	10	_	_	40	50	PKZM4-58		

## Horsepower ratings shown in the table are for reference only.

The final selection of the manual starter depends on the actual motor full load current and service factor on the motor nameplate.

Overload should be set at motor FLA full load current and is calibrated to 1.15 S.F. Specified values to NEC table 430-150.




## **Ordering Instructions**



- Determine the motor FLA and Service Factor.
- Use the application rating guide on next page.
- 3 Locate the desired manual motor controller.
- See pages C15 C28 for auxiliaries and accessories.
- All types have adjustable dial for setting motor full load current. Trip current is 125% of set value. For motors with a service factor (SF) of 1.0, set dial to 90% of motor full load current.
- 2 Maximum three-phase at 480V is 52A; at 600V is 52A.

PKZM4




Dimensions are in millimeters.

Not intended for manufacturing purposes.

## **Manual Motor Controller**

PKZM4-... with Lockable Rotary Handle AK-PKZ0



C39