IEC Power Devices IEC Control Relays Selection Guide C-2000

AC Operated Standard Terminals

		List Price
Contact Configuration	Product Number	GO-10C2
4NO	RL4RA040T*	\$57.00
3NO-1NC	RL4RA031T*	\$57.00
2NO-2NC	RL4RA022T*	\$57.00
4NC	RL4RA004T*	\$57.00

AC Operated with Ring Terminal Capacity

		LIST Price
Contact Configuration	Product Number	GO-10C2
4NO	RL4RA040R*	\$65.00
3NO-1NC	RL4RA031R*	\$65.00
2NO-2NC	RL4RA022R*	\$65.00
4NC	RL4RA004R*	\$65.00

To complete the product number, replace the asterisk (*) with the appropriate digit from the Coil Selection table. Contact Rating: A600, P600.

AC Coil Selection

AC Voltage			
60 Hz	50 Hz	* Coil Suffix	
24	24	1	
48	42	F	
120	110	J	
208	_	L	
277	220/230	N	
240	_	S	
480	380/400	U	
_	415	W	
600	500	Υ	

DC Operated Standard Terminals

		List Price
Contact Configuration	Product Number	GO-10C2
4NO	RL4RD040T#	\$100.00
3NO-1NC	RL4RD031T#	\$100.00
2NO-2NC	RL4RD022T#	\$100.00
4NC	RL4RD004T#	\$100.00

DC Operated with Ring Terminal Capacity

mber GO-10C2
R# \$108.00
R# \$108.00
R# \$108.00
R# \$108.00

To complete the product number, replace the crosshatch (#) with the appropriate digit from the Coil Selection table. Contact Rating: A600, P600.

DC Coil Selection

DC Voltage	#Coil Suffix
12	В
24	D
48	G
125	K
250	T


Deference Dublications

Reference Publications		
Instructions		
GFH-6248	RI Relav	



Control Relay

Control Terminal Relay Markings



RL4R 004

www.geindustrial.com